

Berneer[®]

20m-IR Vandal proof Dome Camera (Shape B)

Features

- 2.5 inch, IR-Vandal proof Dome camera
- Day/night with IR filter
- 3.6mm(6mm, 8mm, 12mm) board lens
- $\Phi 5 \times 23$ PCS IR LED, Longest IR distance: 20 meters
- IR LED turned on or off controlled by CDS
- Power supply DC12V
- Waterproof and dustproof reach IP66 standard



Models

| | |
|-----------------|--|
| BN-0320QHL/SS-B | 540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY 2613 DSP |
| BN-0320QHL/SN-B | 540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP |
| BN-0320HHL/SN-B | 480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP |
| BN-0320EHL/SN-B | 450 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP |
| BN-0320DHL/SS-B | 420 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux |
| BN-0320DHL/HH-B | 420 TV lines, 1/3" Sharp CCD, 0.5Lux |
| BN-0420DHL/HH-B | 420 TV lines, 1/4" Sharp CCD, 0.5Lux |

Specifications



| | |
|-----------------------|---|
| Horizontal Resolution | 540/450/420 TV Lines available |
| Electronic Shutter | PAL=1/50 -1/100,000 sec, NTSC=1/60 -1/100,000 sec |
| Pixel | 540 TV lines PAL: 752×582,NTSC: 768×494(H×V) |
| | 420/450 TV lines PAL: 500×582,NTSC: 510×492(H×V) |
| Lens | 3.6mm(6mm, 8mm, 12mm) board lens |
| IR Distance | 20 meters |
| IR Status | Light below 10 Lux, CDS automatically open |

| | |
|-----------------------|--|
| Power Supply | DC12V |
| Power Consumption | 225-308mA |
| Dimension | 94 ×69mm(Φ×H) |
| Net Weight | 0.385kg |
| Operating Temperature | -10 ~ 50°C (Relative Humidity: 95% max.) |

Dimension

| Back View | Side View |
|-----------|-----------|
| | |

Optional Item

| BN-B160-2 Bracket | Snapshot |
|-------------------|----------|
| | |