

# Berneer<sup>®</sup>

## 25m-IR Waterproof Camera (Shape D)

### Features

- IR-waterproof box camera
- Day/night with IR filter
- 6mm(3.6mm,8mm,12mm) board lens
- $\Phi 5 \times 30$ PCS IR LED, Longest IR distance: 25 meters
- IR LED turned on or off controlled by CDS
- Waterproof and dustproof reaching IP66 standard
- Standard unit comes with adjustable bracket
- Suitable for both indoor and outdoor use



### Models

BN-1325Q/SS-D	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY 2613 DSP
BN-1325Q/SN-D	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1325H/SS-D	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY 2613 DSP
BN-1325H/SN-D	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1325E/SN-D	450 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1325D/SS-D	420 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux
BN-1325D/HH-D	420 TV lines, 1/3" Sharp CCD, 0.5Lux
BN-1425D/HH-D	420 TV lines, 1/4" Sharp CCD, 0.5Lux

### Specifications



Horizontal Resolution	540/480/450/420 TV Lines available
Electronic Shutter	PAL=1/50 -1/100,000 sec, NTSC=1/60 -1/100,000 sec
Pixel	480/540 TV lines PAL: 752×582,NTSC: 768×494(H×V)
	420/450 TV lines PAL: 500×582,NTSC: 510×492(H×V)
Lens	6mm(3.6mm,8mm,12mm) board lens
IR Distance	25 meters
IR Status	Light below 10 Lux, CDS automatically open

Power Supply	DC12V
Power Consumption	249-332mA
Dimension	120 × 74 × 66mm (L×W×H) 169x 74x 127mm(include bracket)
Weight	0.54kg
Operating Temperature	-10 ~ 50°C (Relative Humidity: 95% max.)

## Bracket Dimension

