

Berneer®

30m-IR Varifocal Waterproof Camera (Shape D)

Features

- IR-waterproof box camera
- Day/night with IR filter
- 4-9mm varifocal manual iris lens
- External adjustment for zoom and focus
- $\Phi 5 \times 36$ PCS IR LED, Longest IR distance: 30 meters
- IR LED turned on or off controlled by CDS
- Standard unit comes with adjustable bracket, with cable attached
- Waterproof and dustproof reaching IP66 standard
- Suitable for both indoor and outdoor use



Models

BN-1330QWT/SS-D	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY DSP
BN-1330QWT/SN-D	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1330HWT/SS-D	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY 2613 DSP
BN-1330HWT/SN-D	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1330EWT/SN-D	450 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1330DWT/SS-D	420 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux
BN-1330DWT/HH-D	420 TV lines, 1/3" Sharp CCD, 0.5Lux
BN-1430DWT/HH-D	420 TV lines, 1/4" Sharp CCD, 0.5Lux

Specifications



Horizontal Resolution	540/480/450/420 TV Lines available
Electronic Shutter	PAL=1/50 -1/100,000 sec, NTSC=1/60 -1/100,000 sec
Pixel	480/540 TV lines PAL: 752×582,NTSC: 768×494(H×V)
	420/450 TV lines PAL: 500×582,NTSC: 510×492(H×V)

Lens	4-9mm varifocal manual iris lens
IR Distance	30 meters
IR Status	Light below 10 Lux, CDS automatically open
Power Supply	DC12V
Power Consumption	283-366mA
Dimension	146 × 83 × 80mm(L×W×H)
Net Weight	0.91kg
Operating Temperature	-10 ~ 50°C (Relative Humidity: 95% max.)

Bracket Dimension

Back View	Side View
	