

Berneer[®]

30m-IR Waterproof Camera (Shape A)

Features

- IR-waterproof box camera
- Day/night with IR filter
- 6mm(3.6mm,8mm,12mm) board lens
- $\Phi 5 \times 36$ PCS IR LED, Longest IR distance:30 meters
- IR LED turned on or off controlled by CDS
- Waterproof and dustproof reaching IP66 standard.
- Suitable for both indoor and outdoor use.



Models

BN-1330Q/SS-A	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY DSP
BN-1330Q/SN-A	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1330H/SS-A	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY 2613 DSP
BN-1330H/SN-A	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1330E/SN-A	450 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1330D/SS-A	420 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux
BN-1330D/HH-A	420 TV lines, 1/3" Sharp CCD, 0.5Lux
BN-1430D/HH-A	420 TV lines, 1/4" Sharp CCD, 0.5Lux


Specifications



Horizontal Resolution	540/480/450/420 TV Lines available
Electronic Shutter	PAL=1/50 -1/100,000 sec, NTSC=1/60 -1/100,000 sec
Pixel	480/540 TV lines PAL: 752×582,NTSC: 768×494(H×V)
	420/450 TV lines PAL: 500×582,NTSC: 510×492(H×V)
Lens	6mm(3.6mm,8mm,12mm) board lens
IR Distance	30 meters
IR Status	Light below 10 Lux, CDS automatically open
Power Supply	DC12V

Power Consumption	283-366mA
Dimension	122 × 83 × 83mm(L×W×H)
Net Weight	0.kg
Operating Temperature	-10 ~ 50°C (Relative Humidity: 95% max.)

Dimension

Back View	Side View
	

Optional Items

BN-B170-1 Bracket	Snapshot
