

Berneer[®]

30m-IR Waterproof Camera (Shape G)

Features

- IR-waterproof box camera
- Day/night with IR filter
- 8mm (4mm, 6mm, 12mm) IR lens, CS mount
- $\Phi 5 \times 36$ PCS IR LED, Longest IR distance:30 meters
- IR LED turned on or off controlled by CDS
- Power supply DC12V
- Standard unit comes with adjustable bracket
- Waterproof and dustproof reaching IP66 standard.
- Suitable for both indoor and outdoor use.



Models

BN-1330Q/SS-G	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY DSP
BN-1330Q/SN-G	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1330H/SS-G	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY 2613 DSP
BN-1330H/SN-G	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1330E/SN-G	450 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1330D/SS-G	420 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux
BN-1330D/HH-G	420 TV lines, 1/3" Sharp CCD, 0.5Lux
BN-1430D/HH-G	420 TV lines, 1/4" Sharp CCD, 0.5Lux

Specifications



Horizontal Resolution	540/480/450/420 TV Lines available
Electronic Shutter	PAL=1/50 -1/100,000 sec, NTSC=1/60 -1/100,000 sec
Pixel	480/540 TV lines PAL: 752×582,NTSC: 768×494(H×V)
	420/450 TV lines PAL: 500×582,NTSC: 510×492(H×V)
Lens	8mm IR lens, CS mount
IR Distance	30 meters
IR Status	Light below 10 Lux, CDS automatically open

Power Supply	DC12V
Power Consumption	293-366mA
Dimensions	201 × 76 × 73mm(L×W×H) include bracket
Net Weight	0.565kg
Operating Temperature	-10 ~ 50°C (Relative Humidity: 95% max.)