

Berneer[®]

40m-IR Waterproof Camera (Shape A)

Features

- IR-waterproof box camera
- Day/night with IR filter
- 8mm(12mm, 16mm) board lens
- $\Phi 5 \times 48$ PCS IR LED, Longest IR distance:40 meters
- IR LED turned on or off controlled by CDS
- Waterproof and dustproof reaching IP66 standard.
- Suitable for both indoor and outdoor use.



Models



BN-1340Q/SS-A	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY DSP
BN-1340Q/SN-A	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1340H/SS-A	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY 2613 DSP
BN-1340H/SN-A	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1340E/SN-A	450 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1340D/SS-A	420 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux
BN-1340D/HH-A	420 TV lines, 1/3" Sharp CCD, 0.5Lux
BN-1440D/HH-A	420 TV lines, 1/4" Sharp CCD, 0.5Lux

Specifications

Horizontal Resolution	540/480/450/420 TV Lines available	
Electronic Shutter	PAL=1/50 -1/100,000 sec, NTSC=1/60 -1/100,000 sec	
Pixel	480/540 TV lines	PAL: 752×582,NTSC: 768×494(H×V)
	420/450 TV lines	PAL: 500×582,NTSC: 510×492(H×V)
Lens	8mm(12mm, 16mm) board lens	
IR Distance	40 meters	
IR Status	Light below 10 Lux, CDS automatically open	
Power Supply	DC12V	

Power Consumption	352-435mA
Dimension	122×83 ×83mm(L × W × H)
Net Weight	0.61kg
Operating Temperature	-10 ~ 50°C (Relative Humidity: 95% max.)

Dimension

Back View	Side View
	

Optional Items

BN-B170-1 Bracket	Snapshot
	