

# Berneer<sup>®</sup>

## 40m-IR Waterproof Camera (Shape G)

### Features

- IR-waterproof box camera
- Day/night with IR filter
- 8mm(12mm, 16mm) board lens
- $\Phi 5 \times 48$ PCS IR LED, Longest IR distance:40 meters
- IR LED turned on or off controlled by CDS
- Standard unit comes with adjustable bracket
- Waterproof and dustproof reaching IP66 standard.
- Suitable for both indoor and outdoor use.



### Models

BN-1340Q/SS-G	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY DSP
BN-1340Q/SN-G	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1340H/SS-G	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY 2613 DSP
BN-1340H/SN-G	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1340E/SN-G	450 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1340D/SS-G	420 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux
BN-1340D/HH-G	420 TV lines, 1/3" Sharp CCD, 0.5Lux
BN-1440D/HH-G	420 TV lines, 1/4" Sharp CCD, 0.5Lux

### Specifications

Horizontal Resolution	540/480/450/420 TV Lines available
Electronic Shutter	PAL=1/50 -1/100,000 sec, NTSC=1/60 -1/100,000 sec
Pixel	480/540 TV lines PAL: 752×582,NTSC: 768×494(H×V)
	420/450 TV lines PAL: 500×582,NTSC: 510×492(H×V)
Lens	8mm(12mm, 16mm) board lens
IR Distance	40 meters
IR Status	Light below 10 Lux, CDS automatically open

Power Supply	DC12V
Power Consumption	352-435mA
Dimension	201×76 ×73mm(L × W × H) include bracket
Net Weight	0.54kg
Operating Temperature	-10 ~ 50°C (Relative Humidity: 95% max.)