

# Berneer®

## 40m- IR Vandal proof Dome Camera (Shape B)

### Features

- 3.5 inch, IR-Vandal proof Dome camera
- Day/night with IR filter
- 8mm(3.6mm, 6mm, 12mm, 16mm) board lens
- $\Phi 5 \times 48$ PCS IR LED, Longest IR distance: 40 meters
- IR LED turned on or off controlled by CDS
- Power supply DC12V
- Waterproof and dustproof reach IP66 standard



### Models

BN-0340QHL/SS-B	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY 2613 DSP
BN-0340QHL/SN-B	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-0340HHL/SS-B	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY 2613 DSP
BN-0340HHL/SN-B	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-0340EHL/SN-B	450 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-0340DHL/SS-B	420 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux
BN-0340DHL/HH-B	420 TV lines, 1/3" Sharp CCD, 0.5Lux
BN-0440DHL/HH-B	420 TV lines, 1/4" Sharp CCD, 0.5Lux

### Specifications



Horizontal Resolution	540/480/420 TV Lines available
Electronic Shutter	PAL=1/50 -1/100,000 sec, NTSC=1/60 -1/100,000 sec
Pixel	540/480 TV lines PAL: 752×582,NTSC: 768×494(H ×V)
	450/420 TV lines PAL: 500×582,NTSC: 510×492(H ×V)
Lens	8mm(3.6mm, 6mm, 12mm, 16mm)
IR Distance	40 meters

IR Status	Light below 10 Lux, CDS automatically open
Power Supply	DC12V
Power Consumption	352-435mA
Dimension	119 ×82mm(Φ×H)
Net Weight	0.65kg
Operating Temperature	-10 ~ 50°C (Relative Humidity: 95% max.)

## Dimension

Back View	Side View
	