

# Berneer<sup>®</sup>

## 50m-IR Waterproof Camera (Shape G)

### Features


- IR-waterproof box camera
- Day/night with IR filter
- Built-in 12mm (8mm,12mm,16mm)IR board lens
- $\Phi 8 \times 35$ PCS IR LED, Longest IR distance:50 meters
- IR LED turned on or off controlled by CDS
- Standard unit comes with adjustable bracket with cable attached
- Waterproof and dustproof reaching IP66 standard.
- Suitable for both indoor and outdoor use.



### Models

BN-1350Q/SS-G	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY DSP
BN-1350Q/SN-G	540 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1350H/SS-G	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, SONY 2613 DSP
BN-1350H/SN-G	480 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1350E/SN-G	450 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux, NEXTCHIP DSP
BN-1350D/SS-G	420 TV lines, 1/3" Sony Super HAD CCD, 0.1Lux
BN-1350D/HH-G	420 TV lines, 1/3" Sharp CCD, 0.5Lux
BN-1450D/HH-G	420 TV lines, 1/4" Sharp CCD, 0.5Lux

### Specifications



Horizontal Resolution	540/480/450/420 TV Lines available
Electronic Shutter	PAL=1/50 -1/100,000 sec, NTSC=1/60 -1/100,000 sec
Pixel	480/540 TV lines PAL: 752×582,NTSC: 768×494(H ×V)
	420/450 TV lines PAL: 500×582,NTSC: 510×492(H ×V)
Lens	12mm(6mm, 8mm, 16mm) IR board lens
IR Distance	50 meters
IR Status	Light below 10 Lux, CDS automatically open

Power Supply	DC12V
Power Consumption	425-508mA
Dimension	291×102 ×95mm(L × W × H) Include the bracket
Net Weight	0.895kg
Operating Temperature	-10 ~ 50°C (Relative Humidity: 95% max.)