

Berneer[®]

21 Inch Outdoor Camera Housing

Features

- Body is die-casting aluminum
- Side-opening roof for installing camera easily
- Installation mode: wall mounted
- Use environment: indoor/outdoor
- Protection grade: IP55
- Built In Heater/Blower (Optional)
- Input voltage: AC24V or AC220V or AC110V
- Suitable bracket: BN-B70, BN-B80, BN-B90, BN-B227(with BN-B230)



Specifications

Model	BN-7210	BN-7210SHB
Material	Body: aluminum die-casting, Window: optical glass	
Dimension	562×178×148mm(L×W×H)	
Inner Usable Dimensions	412×136×110 mm (L×W×H)	300×136×110 mm (L×W×H)
Blower & Heater	No	With
Input voltage	AC24V or AC220V or AC110V(Please mark voltage on order)	
Heater Switch	ON:5°C, OFF: 20°C	
Blower Switch	ON: 45°C, OFF: 20°C	
Power Consumption	Heater: 60W , Blower: 3W	
Window Dimension	119×87mm(H)	
Connection Hole	Φ11.9mm x 2mm	
Weight	2.9kg	3.02
Use Environment	Indoor/Outdoor	
Operating Temperature	-10°C~45°C	-25°C~60°C