

# Berneer®

# 4CH B/W Quad Processor BN-B204M

## Features

- Real time display picture
- High resolution
- Video gain adjustable
- Supports sequence switch, single picture, Picture freezing, electronic zoom out and four pictures quads
- Dimensions(mm): 295mm(W)×210mm(D)×45mm(H)
- Weight: 1.3kg
- Power source: DC 12V 500mA



## Specifications

Model	BN-B204M
Video Standard	PAL: 50fields/second/CH, NTSC: 60fields/second/CH
Digital Memory	PAL: 720×576, NTSC: 720×480
Video Input	4loops BNC, 1.0Vp-p composite, individually optional 75ohms
Video output	Main Monitor: 1 loop: 1.0Vp-p 75Ω
VCR Input	BNC 1.0Vp-p 75Ω/S-VHS
VCR output	BNC 1.0Vp-p 75Ω/S-VHS
Alarm Input	4 Active TTL High/Low Input(one mating connector)
Alarm Output	1 Programmable as Normally open or normally close
Alarm Duration	Programmable 0-30seconds
Alarm Mode	Video Loss Alarm, Video Motion Alarm, External Alarm
Display Mode	Single picture, Four pictures, Sequence Switch, Picture freezing, Electronic zoom out
Power Consumption	DC12V 6W
Weight	1.3kg
Operating temperature	-30°C~60°C
Dimensions	295mm(W)×210mm(D)×45mm(H)